



# EC Series Self Contained Gourmet Ice Machines — with Progressive Water Discharge — up to 74kg

ECM 127 AS OX Medium gourmet cube 20g, Ø30mm x 34mm



Medium gourmet cube 20g, 30mm dia x H 34mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 74kg daily production rate
- 39kg storage bin capacity
- · Air cooled version
- Produces individual transparent Gourmet crystal clear supercubes
- · Hydrocarbons R290 refrigerant gas
- XSafe Natural Sanitation System
- PWD-Progressive water discharge: pumps excess residual water up to a distance up to 15 meters
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Simple, reliable electromechanic controls
- Horizontal ice evaporator spray-system technology
- · Resistant stainless steel exterior
- Front access condenser air filter, removable and washable

- Routine maintenance visible alarm light on front panel
- Ergonomically designed ice storage access with disappearing door and door closing movement dampening system
- Includes removable air filter, ice scoop, water and drain hose

















# EC Series Self Contained Gourmet Ice Machines — with Progressive Water Discharge — up to 74kg

### **ECM 127 AS OX**









515

591

#### UNIT OF MEASUREMENT: $\boldsymbol{mm}$

- 1. 25/32" OD OVERFLOW DRAIN
- 2. 3/4" GAS WATER INLET
- 3. 3/4" GAS WATER OUTLET WATER COOLED UNIT ONLY
- 4. 3/4" GAS WATER INLET WATER COOLED UNIT ONLY
- 5. CORD SET

#### Ice production per 24 hours

Ambient temperature / Water temperature

| 10°C / 10°C | 21°C / 10°C | 32°C / 21°C |
|-------------|-------------|-------------|
| 75          | 74          | 60          |

#### Dimensions

Width: 680mm Depth: 600mm

Height: 1009mm (including legs)

Nett weight: 67kg Packed weight: 77kg

#### Water consumption

Air cooled version: 7.4 litres per hour

#### Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 670W,

10A cordset supplied

No. Circuit wire: 3 Compressor: 1400W Energy consumption: 12.9kW/hr

### Refrigerant type

R290

#### Installation distance from wall

Rear 100mm Sides 150mm

Operating requirement air temperature 10-43°C

#### Water connection requirements

Varies Connection: R 34"

Cold water: 5-38°C

Pressure: 100-500kPa

Water outlet connection: ؾ"

Important Notice:

2

3

4

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd

