



EC Series Self Contained Machines – with Progressive Water Discharge – up to 83kg ECM 177 AS OX Medium gourmet cube 20g, Ø30mm x 34mm

Medium gourmet cube 20g, 30mm dia x H 34mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 83kg daily production rate
- 48kg storage bin capacity
- Air cooled version
- Produces individual transparent Gourmet crystal clear supercubes
- Hydrocarbons R290 refrigerant gas
- XSafe Natural Sanitation System
- PWD-Progressive water discharge: pumps excess residual water up to a distance up to 15 meters
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Simple, reliable electromechanic controls
- Horizontal ice evaporator spray-system technology
- Resistant stainless steel exterior
- Front access condenser air filter, removable and washable



- Routine maintenance visible alarm light on front panel
- Ergonomically designed ice storage access with disappearing door and door closing movement dampening system
- Includes removable air filter, ice scoop, water and drain hose





EC Series Self Contained Machines – with Progressive Water Discharge – up to 83kg **ECM 177 AS OX**

680 600 494 990 1079 33 20 66 607 55 33 501 ⊕ ۲ ¢ AIR FLOW ñ 66 116 ⇮ 231 1 UNIT OF MEASUREMENT: mm 340 \Diamond 1. 25/32" OD - OVERFLOW DRAIN 5 2. 3/4" - WATER INLET 384 2 3. 3/4" - WATER OUTLET WATER COOLED UNIT ONLY 515 <⊨ 3 4. 3/4" - WATER INLET 591 WATER COOLED UNIT ONLY 4 5. CORD SET ₽ ☆

Ice production per 24 hours

Ambient temperature / Water temperature 21°C / 10°C 1000 / 1000 3700 / 2100

10 0 / 10 0	21 07 10 0	52 07 21 0
84	83	64

Dimensions Wic

Width:	680mm
Depth:	600mm
Height:	1079mm (including legs)
Nett weight:	77kg
Packed weight:	82kg

Water consumption

Air cooled version: 8.8 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 750W, 10A cordset supplied

No. Circuit wire: 3 Compressor: 1680W Energy consumption: 13.1kW/hr



Installation distance from wall 100mm Rear Sides 150mm Operating requirement air temperature 10-43°C

Water connection requirements Inlet connection: R 3/4" Cold water: 5-38°C 100-500kPa Pressure: Water outlet connection: ؾ"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd AU.SM.2001



sales@wgafoodequip.com.au 02 4228 9733 www.wgafoodequip.com.au