

NW Series Modular Dice Ice Machines – up to 290kg

NW 608 AS OX Dice cube 10g, 22mm x 22mm x 22mm

NWH 608 AS OX Half dice cube 6g, 10mm x 22mm x 28mm



Dice cube 10 g
W 22 x D 22 x H 22 mm



Half dice cube 6 g
W 10 x D 22 x H 28 mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.


- Up to 290kg daily production rate
- Head only ice maker - requires a separate storage bin to store the ice produced
- Air cooled version
- Vertical evaporator spray-system technology
- XSafe - Natural Sanitation System
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- T304 grade stainless steel exterior
- Auto-alert indicator lights to show operation status and maintenance
- One touch cleaning for time and labour saving
- Front evaporator access for easy servicing
- Includes air filter, water and drain hose
- Double stack option available

Recommended storage bins

- NB 393 – 178kg storage capacity
- NB 530 – 243kg storage capacity
- NB 948 with CBT 48 EAMCD cover – 406kg storage capacity

NW Series Modular Dice Ice Machines – up to 290kg

NW 608 AS OX, NWH 608 AS OX



Ice production per 24 hours

Ambient temperature / Water temperature

	10°C / 10°C	21°C / 10°C	32°C / 21°C
NW 608 AS OX	315	290	230
NWH 608 AS OX	320	290	225

Dimensions

Width:	760mm
Depth:	620mm
Height:	575mm
Nett weight:	73kg
Packed weight:	88kg

Water consumption

Air cooled version: 16.9 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 1600W,
10A cordset supplied
No. Circuit wire: 3
Compressor: 48500W
Energy consumption: 36.6kW/hr

Refrigerant type

R404a

Installation distance from wall

Rear 100mm
Sides 150mm
Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R 3/4"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: Ø 20mm

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd
AU.SM.2001