UNDER COUNTER GLASS DOOR _S SERIES

SGR18-3

___ FEATURES / BENEFITS =__

FRONT BREATHING

Our innovative, front breathing feature also allows this model to provide high efficiency in narrow spaces

HOT GAS CONDENSATE SYSTEM

Through SKIPIO's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

SIDE MOUNT COMPRESSOR UNIT

By positioning the compressor on the side of the unit, refrigerators can now be serviced without being moved

■EFFICIENT REFRIGERATION SYSTEM

SKIPIO Undercounter series refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

EXTERIOR & INTERIOR OF THE CABINET

SKIPIO Undercounter series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation

ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience

MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

*ADJUSTABLE, HEAVY DUTY, PE (POLYETHYLENE)

COATED WIRE SHELVES



Model	Doors	Capacity (Liters)	Shelves	Compressor (HP)	Amps (A)	Weight (Kg)	L X D X H (mm)
SGR18-3	3	516	3	1/3	3	127	1800x700(600)x855

Model: SGR18-3


SPEC SHEET	SGR18-3		
Classification	Refrigerator		
Cabinet Dimension (WxDxH mm)	1800x700(600)x855		
Capacity (Liters)	516		
Inner Temperature	1°C~8°C		
Doors	3		
Number of Shelves	3		
Refrigent	R-134a		
Compressor (Hp)	1/3		
Lamp	LED lamp		
Cooling Type	Fan cooling type		
Insulation Type	Polyurethane / Cyclopentane + CFC Free		
Temperature Control Type	Digital		
Amps (A)	3		
Voltage (V/Hz/Ph)	240V 50Hz 1Ph		
Power (W)	366		
Weight (Kg)	127		






PLAN VIEW

(unit: mm)



TOP VIEW























TEL: 02-8798-5061/5283/5581

FAX: 02-8798-5707