

ActiveCore™ 2 Series TME

General Display

Upright fridges
Top mount design

Display and store food, drinks, and perishables, including flowers, chocolates, and wine.

Significantly reduce your refrigeration power bill and save money with ultra-energy efficient ActiveCore technology. These spacious fridges are cooler, quieter, and built to last for busy food service and commercial kitchens.



TME650N-A & TME650N-AC



TME1000N-A & TME1000N-AC



TME1500N-A & TME1500N-AC

Standard Finish: White only

Standard models: 1, 2 & 3 glass door (AC models subject to availability)



Own Me - Use our SKOPE Funding online calculator by visiting skope.com/funding



Restaurants / Cafés



Quick Service Restaurants



Clubs / Pubs / Bars



Hospitality Venues



Accommodation



Medical / Aged Care



Schools



Convenience Stores

Quick Guide

- Premium build quality
- Display & store - food, drinks & perishables
- ActiveCore™ technology
- Market leading energy efficiency
- SKOPE Connected controller
- R290 Natural Refrigerant with minimal environmental impact
- Monitor & control with the SKOPE-connect™ app
- Solid & tropical door options - see SKT series
- Full colour options - see SKT series
- Remote available - see SKT series
- Customisable - see SKT series

Standard Features

Benefits

ActiveCore™ cartridge system	Interchangeable & easy servicing - same cartridge used across all models
Premium energy efficient glass	Double Low-E equivalent
Frameless glass door design	Modern appealing look
SKOPE patented EZI-CLIP	Quick shelf set up & adjustment
Bright LED lighting	Showcasing products inside
Door lock tabs	Extra security
Sign panel	Branding opportunities
Slotted back panel	Chilled air directly onto products
Optimal airflow design	Minimal internal temperature variations
Low noise fan system	Quiet operation

Options

- Lit sign (AC model) - subject to availability, otherwise see SKT series
- Extra shelf & slides/clips
- Gravity feed shelving
- Door hinge kit (1 door models only)



Full Warranty
ActiveCore™ Series



High Efficiency
Major Energy Savings



Compliance
Independently Verified



Food Safe
Keeps food below 5°C

ActiveCore™ 2 Series

TME - Top Mount

Cabinet

Doors	Glass
Cabinet construction	Powdercoated steel
Shelves	Plastic coated wire
Breathes from/Expels to	Upper front/Upper rear
Sign	Sign panel - Lit Sign on AC models if available
Lighting	LED module - 1 per door
Controller	Electronic with SKOPE-connect™
Connectivity	Via Bluetooth
Removable ActiveCore cartridge	Yes

Performance

Temperature Range	Food Safe: 1°C to 4°C (adjustable via SKOPE-connect 1°C to 15°C)
Maximum ambient temperature	43°C (40°C if fridge is built in)
MEPS Category	M1 Food & Drinks
High efficiency model	Yes

Refrigeration

System	ActiveCore™ cartridge - removable unit, top mounted, self contained
Refrigerant	R290 Natural Refrigerant
Drainage	No plumbing required

Electrical

Climate class	5 (40°C/40% RH)
Power Supply	220-240 Volts a.c. 50Hz, single phase supply
Plug	10 Amp 3 pin & 2.3m cable (where applicable cabinets are supplied with correct regional plug types)
Light switch on controller	Yes

Specifications

Model ID	Doors	Sign Type	External Dimensions (W x D x H mm)	Total Floor Area (m ²)	Weight (kg)	Gross Internal Volume (litres)	Total Display Area (m ²)	Adjustable Shelves (No.)	Adjustable Shelves Size (wide x deep mm)	Total Shelf Area (m ²)	Product Facings (600ml PET)	TEC kWh/24h @ Climate Class 3	Refrigerant / Charge	Current Draw (Amps)	Electrical Capacity (kW)
TME650N-A	1	Sign panel	740 x 745 x 2200	0.55	170	610	0.75	5	625 x 470	1.46	40	2.57	R290 / 99g	2.9	0.74
TME650N-AC	1	Lit sign	740 x 745 x 2200	0.55	170	610	0.75	5	625 x 470	1.46	40	2.67	R290 / 99g	2.9	0.74
TME1000N-A	2	Sign panel	1130 x 745 x 2200	0.84	225	980	1.08	5	1015 x 470	2.35	70	3.57	R290 / 99g	3.0	0.74
TME1000N-AC	2	Lit sign	1130 x 745 x 2200	0.84	225	980	1.08	10	500 x 470	2.35	70	3.72	R290 / 99g	3.0	0.74
TME-1500N-A	3	Sign panel	1705 x 745 x 2200	1.27	320	1497	1.67	15	500 x 470 (side), 570 x 470 (middle)	3.69	110	5.71	R290 / 99g	3.4	0.74
TME1500N-AC	3	Lit sign	1705 x 745 x 2200	1.27	320	1497	1.67	15	500 x 470 (side), 570 x 470 (middle)	3.69	110	5.98	R290 / 99g	3.4	0.74

